

Production Range for Boiler Pipes

Outside Diameter		Wall Thickness (mm)																				
(mm)	(inch)	2,60	2,90	3,20	3,60	4,00	4,37	4,50	4,78	5,00	5,20	6,00	6,30	6,50	7,10	8,00	8,80	9,00	10,00	11,00	12,50	13,00
		Mass Per Unit Length (kg/m)																				
Ø21,3	1/2	1,20	1,32	1,43	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Ø26,9	3/4	1,56	1,72	1,87	2,07	2,26	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Ø33,4	1	1,97	2,18	2,38	2,65	2,90	3,13	3,21	3,37	3,50	3,62	-	-	-	-	-	-	-	-	-	-	-
Ø33,7	1	1,99	2,20	2,41	2,67	2,93	3,16	3,24	3,41	3,54	3,65	-	-	-	-	-	-	-	-	-	-	-
Ø42,2	1 1/4	2,54	2,81	3,08	3,43	3,77	4,08	4,18	4,41	4,59	4,74	5,36	5,58	5,72	-	-	-	-	-	-	-	-
Ø42,4	1 1/4	2,55	2,82	3,09	3,44	3,79	4,10	4,21	4,43	4,61	4,77	5,39	5,61	5,75	-	-	-	-	-	-	-	-
Ø48,3	1 1/2	2,93	3,25	3,56	3,97	4,37	4,73	4,86	5,13	5,34	5,53	6,26	6,53	6,70	7,21	-	-	-	-	-	-	-
Ø57,0		3,49	3,87	4,25	4,74	5,23	5,67	5,83	6,16	6,41	6,64	7,55	7,88	8,09	8,74	-	-	-	-	-	-	-
Ø60,3	2	3,70	4,10	4,51	5,03	5,55	6,03	6,19	6,54	6,82	7,07	8,03	8,39	8,62	9,31	-	-	-	-	-	-	-
Ø73,0	2 7/8	4,51	5,01	5,51	6,16	6,81	7,40	7,60	8,04	8,38	8,69	9,91	10,36	10,66	11,54	12,82	13,93	-	-	-	-	-
Ø76,1	2 1/2	4,71	5,23	5,75	6,44	7,11	7,73	7,95	8,41	8,77	9,09	10,37	10,84	11,16	12,08	13,43	14,60	-	-	-	-	-
Ø88,9	3	5,53	6,15	6,76	7,57	8,37	9,11	9,37	9,92	10,34	10,73	12,27	12,83	13,21	14,32	15,96	17,38	-	-	-	-	-
Ø114,3	4	-	7,97	8,77	9,83	10,88	11,85	12,18	12,91	13,48	13,99	16,02	16,78	17,28	18,77	20,97	22,89	23,37	25,72	-	-	-
Ø139,7	5	-	9,78	10,77	12,08	13,39	14,58	15,00	15,90	16,61	17,25	19,78	20,72	21,35	23,22	25,98	28,41	29,01	31,98	-	-	-
Ø165,1	6	-	11,60	12,78	14,34	15,89	17,32	17,82	18,90	19,74	20,50	23,54	24,67	25,42	27,66	30,99	33,92	34,64	38,25	-	-	-
Ø168,3	6	-	11,83	13,03	14,62	16,21	17,67	18,18	19,27	20,13	20,91	24,01	25,17	25,93	28,22	31,62	34,61	35,36	39,04	-	-	-
Ø177,8	7	-	12,51	13,78	15,46	17,14	18,69	19,23	20,39	21,31	22,13	25,42	26,64	27,46	29,89	33,50	36,67	37,46	41,38	-	-	-
Ø193,7	7 5/8	-	-	-	16,88	18,71	20,40	21,00	22,27	23,27	24,17	27,77	29,11	30,01	32,67	36,63	40,12	40,99	45,30	49,56	55,85	57,93
Ø219,1	8	-	-	-	19,13	21,22	23,14	23,81	25,26	26,40	27,43	31,53	33,06	34,08	37,12	41,65	45,64	46,63	51,56	56,45	63,68	66,07
Ø244,5	9	-	-	-	-	23,72	25,88	26,63	28,26	29,53	30,69	35,29	37,01	38,15	41,57	46,66	51,15	52,27	57,83	63,34	71,51	74,21
Ø273,0	10	-	-	-	-	26,53	28,95	29,80	31,62	33,04	34,34	39,51	41,43	42,72	46,56	52,28	57,33	58,59	64,86	71,07	80,30	83,35
Ø323,9	12	-	-	-	-	31,55	34,43	35,44	37,62	39,32	40,87	47,04	49,34	50,88	55,47	62,32	68,38	69,89	77,41	84,88	95,99	99,67
Ø339,7	13 3/8	-	-	-	-	33,11	36,14	37,20	39,48	41,27	42,89	49,37	51,80	53,41	58,23	65,44	71,81	73,40	81,30	89,16	100,86	104,73

Length Range

4,0 - 9,0 m

5,0 - 14,0 m