

Certificate of Conformity of the Factory Production Control

2195-CPR-1629401

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

Cold formed welded structural hollow sections of non-alloy steels made of the following steel grades

(tested for performance for the characteristics described in Annex 1 which is an inseparable part of this certificate)

produced by the manufacturer

TOSÇELİK PROFİL VE SAC END. A.Ş.

Organize Sanayi Böl. Necati Özsoy Cad. No:12, 31200 İskenderun / Hatay – Turkey

and produced in the manufacturing plant

TOSÇELİK PROFİL VE SAC END. A.Ş.

Organize Sanayi Böl. 5. Kısım 5007. Sok. No:22 Dilovası / Kocaeli – Turkey

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s)

EN 10219-1: 2006

It is proof that the performance characteristics specified in the audit report numbered CPR-089/25, which is an integral part of this certificate and is annexed to this certificate under system 2+, are implemented and that all requirements of the Factory Production Control determined for these performances are compliant. This certificate was first issued on 20.10.2016, renewed on 20.10.2025 and will remain valid as long as neither the harmonised standard, the construction product, the assessment and verification of constancy of performance methods nor the manufacturing conditions and factory production control in the factory are modified significantly, unless suspended or withdrawn by the notified factory production control certification body. The certificate is supported through annual surveillance audit and is reissued after each surveillance audit.

Validity Date : 20.10.2027

Period Validity Date : 20.10.2026



Rukiye BALKAN
Deputy General Manager



FR. CPR. 24 R:05

Certificate of Conformity of the Factory Production Control

2195-CPR-1629401

Annex 1


Intended uses;

To be used in metal structures or in composite metal and concrete structures.

Controlled Performance Characteristics;

- Dimension and Shape Tolerances,
- Yield Strength,
- Elongation,
- Tensile Strength,
- Impact Resistance,
- Weldability.

Steel Grade	Section	Dimensions
S235JRH S275J0H S275J2H S275NH S275NLH S275MH S275MLH S355J0H S355J2H S355K2H S355NH S355NLH S355MH S355MLH S420MH S420MLH S460NH S460NLH S460MH S460MLH	Circular hollow sections	Ø from 17,20 mm up to 273,00 mm wall thickness: from 0,60 mm up to 10,00 mm
	Square hollow sections	from 10 mm x 10 mm up to 200 mm x 200 mm, wall thickness: from 0,60 mm up to 10,00 mm
	Rectangular hollow sections	from 10 mm x 15 mm up to 150 mm x 250 mm, wall thickness: from 0,60 mm up to 10,00 mm


Rukiye BALKAN
Deputy General Manager

FR. CPR. 24 R:05