



Production Range for Casing, Tubing and Drill Rod Pipes

Production Range for
API 5CT / Casing Pipes

Production Range for
API 5CT / Tubing Pipes

Production Range for
Drill Rod Pipes

Production Range for API 5CT / Casing Pipes

Outside Diameter		Wall Thickness (mm)		Mass Per Unit Length	Hydrostatic Test Pressure (bar)		
(inch)	(mm)	(inch)	(mm)	(kg/m)	H40	J55	K55
4 1/2	Ø114,3	0,205	5,21	14,38	201	276	276
		0,224	5,69	15,73	220	302	302
		0,250	6,35	17,38	245	337	337
		0,290	7,37	19,87	285	391	391
		0,337	8,56	22,69	331	454	454
5	Ø127,0	0,220	5,59	17,19	194	267	267
		0,253	6,43	19,69	224	307	307
		0,296	7,52	22,69	261	359	359
		0,362	9,19	27,19	320	439	439
5 1/2	Ø139,7	0,244	6,20	20,91	196	269	269
		0,275	6,98	23,48	221	303	303
		0,304	7,72	25,72	244	335	335
		0,361	9,17	30,05	290	398	398
6 5/8	Ø168,28	0,288	7,32	29,76	192	264	264
		0,352	8,94	35,72	235	322	322
		0,417	10,59	41,67	278	382	382
		0,475	12,06	47,62	316	435	435
7	Ø177,8	0,231	5,87	25,60	146	200	200
		0,272	6,91	29,91	172	236	236
		0,317	8,05	34,67	200	275	275
		0,362	9,19	39,14	228	313	313
		0,408	10,36	43,60	257	353	353
		0,453	11,51	47,92	286	393	393
7 5/8	Ø193,68	0,498	12,65	52,09	314	431	431
		0,300	7,62	35,72	174	239	239
		0,328	8,33	39,29	190	261	261
		0,375	9,52	44,20	217	298	298
		0,430	10,92	50,15	249	342	342
8 5/8	Ø219,08	0,500	12,70	58,04	290	398	398
		0,264	6,71	35,72	135	186	186
		0,304	7,72	41,67	156	214	214
		0,352	8,94	47,62	180	247	247
		0,400	10,16	53,57	205	281	281
		0,450	11,43	59,53	230	316	316
9 5/8	Ø244,48	0,500	12,70	65,48	256	351	351
		0,312	7,92	48,07	143	196	196
		0,352	8,94	53,57	161	222	222
		0,395	10,03	59,53	181	249	249
		0,435	11,05	64,73	200	274	274
10 3/4	Ø273,05	0,472	11,99	69,94	217	297	297
		0,279	7,09	48,74	86	118	118
		0,350	8,89	60,27	108	148	148
		0,400	10,16	67,71	123	169	169
		0,450	11,43	75,90	139	190	190
13 3/8	Ø339,72	0,495	12,57	82,59	152	209	209
		0,330	8,38	71,43	82	112	112
		0,380	9,65	81,10	94	129	129
		0,430	10,92	90,78	106	146	146
		0,480	12,19	101,19	119	163	163
		0,514	13,06	107,15	127	175	175

Length Range

5,0 - 14,0 m



Production Range for API 5CT / Tubing Pipes

Outside Diameter		Wall Thickness (mm)		Mass Per Unit Length	Hydrostatic Test Pressure (bar)		
(inch)	(mm)	(inch)	(mm)	(kg/m)	H40	J55	K55
1.050	Ø26,67	0,113	2,87	1,70	475	-	-
1.315	Ø33,4	0,133	3,38	2,53	447	-	-
1.660	Ø42,16	0,125	3,18	3,06	333	457	457
		0,140	3,56	3,42	373	-	-
1.900	Ø48,26	0,125	3,18	3,54	291	400	400
		0,145	3,68	4,09	337	462	462
		0,200	5,08	5,43	465	-	-
2 3/8	Ø60,32	0,167	4,24	5,95	310	426	426
		0,190	4,83	6,85	354	486	486
		0,254	6,45	8,63	472	-	-
2 7/8	Ø73,02	0,217	5,51	9,52	333	458	458
		0,276	7,01	11,61	424	-	-
		0,308	7,82	12,80	473	-	-
3 1/2	Ø88,9	0,216	5,49	11,46	273	374	374
		0,254	6,45	13,69	320	440	440
		0,289	7,34	15,18	365	-	-
4	Ø101,6	0,226	5,74	14,14	249	343	343
		0,262	6,65	15,57	289	397	397
		0,330	8,38	19,64	364	500	500
4 1/2	Ø114,3	0,271	6,88	18,75	266	365	365
		0,337	8,56	22,62	331	454	454
		0,380	9,65	25,30	373	-	-

Length Range

	4,5 - 8,5 m
	5,0 - 14,0 m



Production Range for Drill Rod Pipes

Diameter	Outside Diameter (mm)	Internal Diameter (mm)	Length (mm)
PQ	Ø114,3	Ø101,6	3050
HQ	Ø88,9	Ø77,8	3050
NQ	Ø69,9	Ø60,3	3050

