

Production Range For Special Shaped Hollow Section

Type	Outside Diameter (mm) (AXBXC)	Wall Thickness (mm)											
		0,50	0,60	0,70	0,80	0,90	1,00	1,20	1,40	1,50	2,00	2,50	3,00
		Mass Per Unit Length (kg/m)											
Oval Section	30X15	0,31	0,38	0,43	0,50	0,55	0,61	0,73	0,84	0,89	1,18	1,45	1,72
Oval Section	40X16	-	0,48	0,55	0,64	0,72	0,80	0,95	1,11	1,19	1,55	1,88	2,21
Oval Section	40X20	-	0,51	0,59	0,68	0,76	0,84	1,00	1,16	1,24	1,63	1,98	2,23
Oval Section	50X25	-	-	-	0,82	0,91	1,01	1,22	1,41	1,51	1,99	2,47	2,94
Oval Section	50X32	-	-	-	0,87	0,97	1,08	1,29	1,49	1,60	2,12	2,63	3,13
Elliptical Section	40X20	-	0,47	0,55	0,62	0,70	0,78	0,92	1,07	1,14	1,51	1,86	2,21
D-Section	40X30	-	-	-	0,80	0,90	0,99	1,19	1,38	1,47	1,95	2,41	2,87
28 L-Section	12.5 x 25 x 28	-	-	-	-	-	-	1,24	1,41	1,53	2,03	2,46	3,01
28 T-Section	12.5 x 25 x 28	-	-	-	-	-	-	1,45	1,71	1,80	2,39	2,99	3,56
28 Z-Section	12.5 x 25 x 28	-	-	-	-	-	-	1,45	1,71	1,80	2,39	2,99	3,56
33 L-Section	15 x 30 x 33	-	-	-	-	-	-	1,45	1,71	1,80	2,39	2,99	3,56
33 T-Section	15 x 30 x 33	-	-	-	-	-	-	1,74	2,03	2,16	2,86	3,56	4,26
33 Z-Section	15 x 30 x 33	-	-	-	-	-	-	1,74	2,03	2,16	2,86	3,56	4,26
Octagonal Section	140x140	-	-	-	-	-	-	-	-	-	7,28	9,11	10,89

Length Range

	4,0 - 8,5 m		4,0 - 13,0 m
--	-------------	--	--------------